

FS 400, 450 & 500 Heat Transfer Oil

Description

FS Heat Transfer Oil provides oxidation and thermal stability in vented systems at continuous temperatures up to 600° F (316°C). FS Heat Transfer Oil is formulated with materials that have fewer tendencies to form coke, lacquers and other residues. FS Heat Transfer Oil is non-toxic.

Typical Properties:

Particulates: Substantially Free

Appearance: Clear Amber Liquid

Test / Description	Specification		
	400	450	500
ISO Grade	32	46	68
Viscosity SUS @ 100°F	150.5	214	315
Specific Gravity	0.886	0.8665	0.8772
Flash Point (ASTM D92)	390°F Min.	390°F Min.	390°F Min.
Fire Point (ASTM D92)	430°F Min.	430°F Min.	430°F Min.
Viscosity Index	95	119	105

Product Availability:

FS 400 Heat Transfer Fluid ISO 32

5 Gal. Pail Item #150835
55-gal. Drum Item #151083
265-gal. Totes Item #157519
Bulk Item #227635

FS 450 Heat Transfer Fluid ISO 46

55-gal. Drum Item #227134
Bulk Item #227133

FS 500 Heat Transfer Fluid ISO 68

5 Gal. Pail Item #208598
55-gal. Drum Item #157707
265-gal. Totes Item #157708
Bulk Item #216912

